

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 October 2003 (02.10.2003)

PCT

(10) International Publication Number
WO 03/080230 A1

(51) International Patent Classification⁷: B01J 8/02

(21) International Application Number: PCT/JP03/03591

(22) International Filing Date: 25 March 2003 (25.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002-085149 26 March 2002 (26.03.2002) JP
60/368,965 2 April 2002 (02.04.2002) US

(71) Applicant (for all designated States except US): SHOWA DENKO K. K. [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HOTTA, Masatoshi [JP/JP]; c/o Production & Technology Control, Department, Gases & Chemicals Division, Showa Denko K. K.,

5-1, Ogimachi, Kawasaki-ku, Kawasaki-shi, Kanagawa 210-0867 (JP). ATOBE, Hitoshi [JP/JP]; c/o Production & Technology Control, Department, Gases & Chemicals Division, Showa Denko K. K., 5-1, Ogimachi, Kawasaki-ku, Kawasaki-shi, Kanagawa 210-0867 (JP).


(74) Agent: OHIE, Kunihi; Ohie Patent Office, Horiguchi No.2 Bldg., 7F, 2-6, Nihonbashi-Ningyocho 2-chome, Chuo-ku, Tokyo 103-0013 (JP).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, ME, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: REACTION APPARATUS WITH A HEAT-EXCHANGER



(57) Abstract: A reaction apparatus comprising a heat exchanger 5 and a reactor 1 with a heater 2, which are enclosed in an outer casing 6, the top of the heat exchanger 5 being connected to the reactor 1, the other end part of the heat exchanger 5 and the bottom of the outer casing 6 being fixed to each other by a flange 4, and a double piping 7 for introducing a gas to be treated and discharging the treated gas being connected to the other end part of the heat exchanger 5, such that the gas passes through the heat exchanger 5, the reactor 1 and the heat exchanger 5 during the process from introducing gas through one of the inner tube and the outer tube in the double piping to discharging the gas through the other tube, and reaction method using the apparatus. Using the apparatus of the present invention, the temperature distribution inside the reactor can be kept uniform and efficiency in energy recovery is enhanced.

BEST AVAILABLE COPY